

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/060631 A2

(51) International Patent Classification: Not classified

(21) International Application Number:
PCT/US2004/041623

(22) International Filing Date:
13 December 2004 (13.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/528,660 11 December 2003 (11.12.2003) US

(71) Applicant (for all designated States except US): **OHIO UNIVERSITY** [US/US]; 20 East Circle Drive, Suite 190, Athens, Ohio 45701-3751 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MIRACLE, Dr. Daniel B.** [US/US]; 2237 Shadowood Circle, Bellbrook, Ohio 45305 (US). **TAMIRISAKANDALA, Dr. Seshacharyulu** [IN/US]; 2444 Mallard Lane, Apt. #3,

Beavercreek, Ohio 45431 (US). **BHAT, Dr. Radhakrishna B.** [IN/US]; 2388 Edgewater Drive, Beavercreek, Ohio 45431 (US). **TILEY, Dr. Jaimie S.** [US/US]; 220 South State Street, Verona, Ohio 45309 (US).


(74) Agent: **FROST, Kristin J.**; 800 Superior Avenue, Suite 1400, Cleveland, Ohio 44114-2688 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: TITANIUM ALLOY MICROSTRUCTURAL REFINEMENT METHOD AND HIGH TEMPERATURE, HIGH STRAIN RATE SUPERPLASTIC FORMING OF TITANIUM ALLOYS



(57) Abstract: A method for refining the microstructure of titanium alloys in a single thermomechanical processing step, wherein the titanium alloy comprises boron. In some embodiments, the method comprises the steps of first adding boron to the titanium alloy then subjecting the boron-containing titanium alloy to a thermomechanical processing step. Also provided is a method for achieving superplasticity in titanium alloys comprising the steps of selecting a boron-containing titanium alloy, determining the temperature and strain rate necessary to achieve beta superplasticity, and applying sufficient temperature and strain rate to the boron-containing titanium alloy to deform the alloy to the desired shape. Also provided methods of forming titanium alloy parts and the parts prepared by these methods.



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*